

View Online at <https://aerobasegroup.com/nsn/5930-00-811-8389>

**Thread Class:**

2b 2nd mounting facility

**Hazardous Locations/environmental Protection:**

Dustproof

**Overall Length:**

7.697 inches

**Overall Height:**

3.750 inches

**Overall Width:**

3.375 inches

**Shaft Diameter:**

0.250 inches single actuator

**Shaft Length:**

0.375 inches single actuator

**Unthreaded Mounting Hole Diameter:**

0.213 inches 1st mounting facility

**Individual Section Quantity:**

15

**Longest Horizontal Distance Between Mounting Centers:**

3.219 inches 1st mounting facility

**Longest Vertical Distance Between Mounting Centers:**

3.219 inches 1st mounting facility

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

2 each section rear

**Throw Quantity:**

1 each section rear

**Mounting Method:**

Bracket 2nd mounting facility and threaded hole 2nd mounting facility

**Features Provided:**

Actuator knob

**Thread Size:**

0.250 inches 2nd mounting facility

**Contact Voltage Rating In Volts:**

450.0 ac at sea level

**Mounting Facility Pattern:**

Four position rectangular 1st mounting facility

**Switch Actuator Indexing Position Quantity:**

1 single actuator

**Shaft Type:**

Round single actuator

**Terminal Type:**

Screw

**Contact Switching Action:**

Makes before breaks each section rear

**Switch Actuator Positioning Increment:**

90.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

30.0 amperes resistive load dc at sea level

**Style Designator:**

Tap, circuit selector

**Thread Series Designator:**

Unc 2nd mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0