NSN 5930-00-812-1126

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-812-1126

Overall Length:
1.250 inches
Overall Height:
0.440 inches
Overall Width:
0.401 inches
Mounting Slot Width:
0.125 inches
Body Length:
0.776 inches
Body Width:
0.375 inches
Body Height:
0.251 inches
Distance Between Mounting Facility Centers:
1.000 inches
Tempurature Sensing Element Type:
Expanding shell
Operating Tempurature Rating:
Between -40.0 degrees fahrenheit and 220.0 degrees fahrenheit
Mounting Method:
Clip and slot
Features Provided:
Hermetically sealed case
Contact Action Stimulus:
Increase
Mounting Facility Pattern:
Two position in-line
Nonpile-up Contact Arrangement:
and the comment of th
1 pole, single throw, normally closed, momentary action
1 pole, single throw, normally closed, momentary action
1 pole, single throw, normally closed, momentary action Terminal Type:
1 pole, single throw, normally closed, momentary action Terminal Type: Tab, solder lug
1 pole, single throw, normally closed, momentary action Terminal Type: Tab, solder lug Contact Load Current Rating:
1 pole, single throw, normally closed, momentary action Terminal Type: Tab, solder lug Contact Load Current Rating: 2.5 amperes resistive load first voltage
1 pole, single throw, normally closed, momentary action Terminal Type: Tab, solder lug Contact Load Current Rating: 2.5 amperes resistive load first voltage Contact Adjustability:
1 pole, single throw, normally closed, momentary action Terminal Type: Tab, solder lug Contact Load Current Rating: 2.5 amperes resistive load first voltage Contact Adjustability: Actuation point adjustable, preset
1 pole, single throw, normally closed, momentary action Terminal Type: Tab, solder lug Contact Load Current Rating: 2.5 amperes resistive load first voltage Contact Adjustability: Actuation point adjustable, preset Contact Adjustment Range:

Contact Stimulus Rating:

140.00 actuation point degrees fahrenheit

NSN 5930-00-812-1126

Thermostatic Switch - Page 2 of 2



Contact Vo	ltage	Rating	ln '	Vol	ts:
------------	-------	--------	------	-----	-----

28.0 dc at sea level second voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular w/bracket

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0