NSN 5930-00-813-9708

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-813-9708

Hazardous Locations/environmental Protection:
Dustproof
Overall Length:
4.094 inches
Overall Height:
2.125 inches
Overall Width:
1.812 inches
Shaft Diameter:
0.375 inches single actuator
Shaft Length:
0.750 inches single actuator
Unthreaded Mounting Hole Diameter:
0.188 inches single mounting facility
Individual Section Quantity:
7
Longest Horizontal Distance Between Mounting Centers:
1.437 inches single mounting facility
Longest Vertical Distance Between Mounting Centers:
1.750 inches single mounting facility
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
1 each section rear
Throw Quantity:
5 each section rear
Mounting Method:
Unthreaded hole single mounting facility
Contact Voltage Rating In Volts:
30.0 lowest dc voltage rating at sea level
Mounting Facility Pattern:
Four position rectangular single mounting facility
Switch Actuator Indexing Position Quantity:
8 single actuator
Shaft Type:
Round, slotted single actuator
Terminal Type:
Tab w/screw
Contact Switching Action:
Breaks before makes each section rear
Switch Actuator Positioning Increment:
45.0 degrees single actuator

45.0 degrees single actuator

NSN 5930-00-813-9708

Rotary Switch - Page 2 of 2



Switch Actuator St	p Device Type:
--------------------	----------------

Adjustable stop single actuator

Contact Load Current Rating:

5.0 amperes resistive load lowest dc voltage rating at sea level and 2.5 amperes inductive load lowest dc voltage rating at sea level

Style Designator:

Tap, circuit selector

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0