## NSN 5930-00-814-2607

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-814-2607
Body Style:
Hole mounted
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.797 inches
Body Length:
1.378 inches
Body Width:
0.406 inches
Body Height:
0.958 inches
Unthreaded Mounting Hole Diameter:
0.113 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.406 inches
Actuator Length:
0.875 inches
Actuator Style:
Leaf
Actuator Free Position Height:
0.645 inches
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
End Application:
B-52, ac, mc, ec, hc, c-130
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:
3.0 ounces
Criticality Code Justification:
Feat
Switch Actuating Force:
16.0 ounces
Actuator Movement:
0.025 pretravel inches and 0.015 overtravel inches and 0.020 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
10.000 amperes resistive dc and 5.000 amperes inductive dc and 3.000 amperes lamp dc and 10.000 amperes resistive ac and 5.000
amperes inductive ac and 3.000 amperes lamp ac

## **Special Features:**

Weapon system essential

## NSN 5930-00-814-2607

Sensitive Switch - Page 2 of 2



Terminal Type And Quantity:
3 wire lead
Shelf Life:

N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0