

View Online at <https://aerobasegroup.com/nsn/5930-00-814-6845>

Thread Class:

2a single mounting facility

Thread Length:

0.380 inches single mounting facility

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

3.380 inches

Overall Height:

1.310 inches

Overall Width:

1.120 inches

First Flat Length:

0.250 inches single actuator

Flat Height:

0.218 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.760 inches single actuator

Nonturn Device Radius:

0.530 inches at 9: 00 o'clock

Individual Section Quantity:

9

Nonturn Device Type:

Tab at 9: 00 o'clock

Operating Temperature Range:

-65.0/+125.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section front

Throw Quantity:

11 each section front

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

30.0 dc at sea level

Shaft Flat/slot Angular Location:

135.0 degrees from contact position 1 single actuator

Switch Actuator Indexing Position Quantity:

11 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes each section front

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Contact Load Current Rating:

500.0 milliamperes resistive load dc at sea level and 50.0 milliamperes inductive load dc at sea level

Style Designator:

Tap, circuit selector

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0