NSN 5930-00-814-6903

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-814-6903

Body Style:

Bushing mounted

Overall Length:

3.640 inches

Overall Height:

1.000 inches

Overall Width:

1.000 inches

Body Diameter:

1.000 inches

Bushing Length:

0.970 inches

Body Length:

1.500 inches

Actuator Style:

Roller plunger

Actuator Free Position Height:

2.140 inches

Actuator Roller Diameter:

0.500 inches

Actuator Roller Width:

0.180 inches

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Hermetically sealed

Mounting Method:

Threaded bushing

Features Provided:

Actuator seal

Thread Size:

0.750 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, both positions maintained single switch unit

Switch Release Force:

80.0 ounces

Switch Actuating Force:

Between 96.0 ounces and 192.0 ounces

Actuator Movement:

Between 0.050 pretravel inches and 0.250 overtravel inches and 0.015 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 2.000 amperes inductive dc and 1.000 amperes resistive ac and 1.000 amperes inductive ac

NSN 5930-00-814-6903

Sensitive Switch - Page 2 of 2

Thread Series Designator:

Unef

Terminal Type And Quantity:

6 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0

