NSN 5930-00-814-6903

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-814-6903

Body Style:
Bushing mounted
Overall Length:
3.640 inches
Overall Height:
1.000 inches
Overall Width:
1.000 inches
Body Diameter:
1.000 inches
Bushing Length:
0.970 inches
Body Length:
1.500 inches
Actuator Style:
Roller plunger
Actuator Free Position Height:
2.140 inches
Actuator Roller Diameter:
0.500 inches
Actuator Roller Width:
0.180 inches
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Inclosure Type:
Hermetically sealed
Mounting Method:
Threaded bushing
Features Provided:
Actuator seal
Thread Size:
0.750 inches
Nonpile-up Contact Arrangement:
2 pole, double throw, both positions maintained single switch unit
Switch Release Force:
80.0 ounces
Switch Actuating Force:
Between 96.0 ounces and 192.0 ounces
A atrest an Marramant

Actuator Movement:

Between 0.050 pretravel inches and 0.250 overtravel inches and 0.015 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 2.000 amperes inductive dc and 1.000 amperes resistive ac and 1.000 amperes inductive ac

NSN 5930-00-814-6903 Sensitive Switch - Page 2 of 2



Thread Series Designator:
Unef
Terminal Type And Quantity:
6 screw
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A053a0