NSN 5930-00-815-0320

Flow Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-815-0320 **Overall Length:** 2.250 inches **Overall Height:** 0.812 inches Overall Width: 0.562 inches **Body Length:** 1.062 inches **Unthreaded Mounting Hole Diameter:** 0.120 inches **Longest Horizontal Distance Between Mounting Centers:** 0.750 inches **Longest Vertical Distance Between Mounting Centers:** 0.500 inches **Operating Tempurature Rating:** 130.0 degrees fahrenheit and -65.0 degrees fahrenheit **Mounting Method:** Unthreaded hole **Contact Action Stimulus:** Increase **Mounting Facility Pattern:** Two position diagonal **Nonpile-up Contact Arrangement:** 1 pole, double throw, one position momentary **Terminal Type:** Tab, solder lug **Contact Load Current Rating:** 5.0 amperes resistive load first voltage **Contact Adjustability:** Deactuation point not adjustable and actuation point not adjustable **Contact Stimulus Rating:** 2340.00 actuation point feet per minute and 2120.00 deactuation point feet per minute and 320.00 differential point feet per minute **Contact Voltage Rating In Volts:** 28.0 dc at sea level second voltage Frequency In Hertz: 60.0 single voltage Media For Which Designed:

Gas or liquid

Precious Material And Location:

Precious Material And Location

Contacts silver

Precious Material:

Silver

NSN 5930-00-815-0320

Flow Switch - Page 2 of 2



Style Designator:
Rectangular
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A048b0