## NSN 5930-00-815-4161

Sensitive Switch - Page 1 of 2

Between 0.998 inches and 1.000 inches

**Body Style:**Hole mounted

**Body Length:** 

N/a



View Online at https://aerobasegroup.com/nsn/5930-00-815-4161

**Center To Center Distance Between Mounting Facilities Parallel To Length:** 

1.940 inches
Body Width:
Between 0.677 inches and 0.697 inches
Body Height:
1.060 inches
Case Material:
Plastic
Unthreaded Mounting Hole Diameter:
Between 0.139 inches and 0.142 inches
Actuator Length:
2.500 inches
Actuator Style:
Leaf
Actuator Width:
0.190 inches
Actuator Free Position Height:
Between 1.030 inches and 1.090 inches
Maximum Voltage Rating In Volts:
460.0 ac and 250.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:
0.5 ounces
Switch Actuating Force:
Between 1.0 ounces and 2.5 ounces
Actuator Movement:
Between 0.281 pretravel inches and 0.406 pretravel inches
Contact Load Current Rating At Maximum Rated Voltage:
250.000 milliamperes resistive dc and 15.000 amperes resistive ac
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:

## NSN 5930-00-815-4161

Sensitive Switch - Page 2 of 2



	Of			

--

Demilitarization:

No

Fiig:

A053a0