NSN 5930-00-816-0047



| Thermostatic Switch - Page 1 of 2 |
|---|
| View Online at https://aerobasegroup.com/nsn/5930-00-816-0047 |
| Overall Height: |
| 0.607 inches |
| Body Diameter: |
| 0.475 inches |
| Mounting Slot Width: |
| 0.156 inches |
| Body Height: |
| 0.315 inches |
| Distance Between Mounting Facility Centers: |
| 1.062 inches |
| Tempurature Sensing Element Type: |
| Internal sensor |
| Mounting Method: |
| Bracket and slot |
| Features Provided: |
| Tamper proof cap |
| Contact Action Stimulus: |
| Increase |
| Mounting Facility Pattern: |
| Two position in-line |
| Nonpile-up Contact Arrangement: |
| 1 pole, single throw, normally closed, momentary action |
| Terminal Type: |
| Tab, solder lug |
| Contact Load Current Rating: |
| 5.0 amperes resistive load third voltage |
| Contact Adjustability: |
| Deactuation point not adjustable and actuation point not adjustable |
| Contact Stimulus Rating: |
| 120.00 actuation point degrees fahrenheit and 248.00 deactuation point degrees fahrenheit |
| Contact Voltage Rating In Volts: |
| 30.0 ac at sea level third voltage |
| Media For Which Designed: |
| Gas or liquid |
| Style Designator: |
| Disc w/flange |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

No

NSN 5930-00-816-0047 Thermostatic Switch - Page 2 of 2

Fiig: A048b0

