

View Online at <https://aerobasegroup.com/nsn/5930-00-816-1265>

**Hazardous Locations/environmental Protection:**

Watertight

**Overall Length:**

3.593 inches

**Overall Height:**

2.500 inches

**Overall Width:**

2.500 inches

**First Flat Length:**

0.750 inches single actuator

**Flat Height:**

0.219 inches single actuator

**Shaft Diameter:**

0.250 inches single actuator

**Shaft Length:**

1.437 inches single actuator

**Unthreaded Mounting Hole Diameter:**

0.234 inches single mounting facility

**Individual Section Quantity:**

2

**Knob Manufacturer Code:**

82121

**Longest Horizontal Distance Between Mounting Centers:**

1.640 inches single mounting facility

**Longest Vertical Distance Between Mounting Centers:**

1.640 inches single mounting facility

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 each section front

**Throw Quantity:**

3 each section rear

**Mounting Method:**

Unthreaded hole single mounting facility

**Features Provided:**

Actuator knob

**Contact Voltage Rating In Volts:**

450.0 highest ac voltage rating at sea level

**Rotor Through Connection Quantity:**

1 each section

**Mounting Facility Pattern:**

Four position rectangular single mounting facility

**Switch Actuator Indexing Position Quantity:**

4 single actuator

**Shaft Type:**

Round, flatted, threaded hole single actuator

**Terminal Type:**

Tab w/screw

**Contact Switching Action:**

Breaks before makes each section rear

**Switch Actuator Positioning Increment:**

90.0 degrees single actuator

**Contact Load Current Rating:**

5.0 amperes resistive load dc at sea level

**Style Designator:**

Tap, circuit selector

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0