

View Online at <https://aerobasegroup.com/nsn/5930-00-817-2742>

Thread Length:

0.250 inches single mounting facility

Overall Length:

2.375 inches

Overall Height:

1.875 inches

Overall Width:

1.625 inches

First Flat Length:

0.438 inches single actuator

Flat Height:

0.203 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.750 inches single actuator

Individual Section Quantity:

2

Nonturn Device Type:

Tab at 2: 00 o'clock

Switch Contact Basic Design:

Nonpile-up symmetrical and nonpile-up nonsymmetrical

Pole Quantity:

1 1st section front

Throw Quantity:

4 1st section front

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

15.0 dc at sea level

Shaft Flat/slot Angular Location:

350.0 degrees from nonturn device single actuator

Switch Actuator Indexing Position Quantity:

4 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes 1st section front

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Contact Load Current Rating:

0.5 amperes resistive load ac at sea level

Special Features:

W/locking device

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0