NSN 5930-00-817-3784

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-817-3784

| view Offiline at https://aerobasegroup.com/hsh/5550-00-017-5704 |
|--|
| Overall Length: |
| 1.250 inches |
| Overall Height: |
| 0.640 inches |
| Body Diameter: |
| 0.563 inches |
| Body Height: |
| 0.380 inches |
| Unthreaded Mounting Hole Diameter: |
| 0.140 inches |
| Distance Between Mounting Facility Centers: |
| 0.938 inches |
| Tempurature Sensing Element Type: |
| Internal sensor |
| Mounting Method: |
| Bracket and unthreaded hole |
| Features Provided: |
| Hermetically sealed case |
| Contact Action Stimulus: |
| Increase |
| Mounting Facility Pattern: |
| Two position in-line |
| Nonpile-up Contact Arrangement: |
| 1 pole, single throw, normally closed, momentary action |
| Terminal Type: |
| Tab, solder lug |
| Contact Load Current Rating: |
| 5.0 amperes resistive load single voltage and 500.0 milliamperes inductive load single voltage |
| Contact Adjustability: |
| Deactuation point not adjustable and actuation point not adjustable |
| Contact Stimulus Rating: |
| 130.00 actuation point degrees fahrenheit and 115.00 deactuation point degrees fahrenheit |
| Contact Voltage Rating In Volts: |
| 28.0 dc at sea level single voltage |
| Media For Which Designed: |
| Gas or liquid |
| Style Designator: |
| Disc w/flange |
| Shelf Life: |
| N/a |

Unit Of Measure:

NSN 5930-00-817-3784

Thermostatic Switch - Page 2 of 2



Demilitarization:

No

Fiig:

A048b0