

View Online at <https://aerobasegroup.com/nsn/5930-00-817-3788>

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

2.720 inches

Overall Height:

1.750 inches

Overall Width:

1.750 inches

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.250 inches single actuator

Unthreaded Mounting Hole Diameter:

0.134 inches single mounting facility and 0.154 inches single mounting facility

Individual Section Quantity:

2

Longest Horizontal Distance Between Mounting Centers:

1.250 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

1.250 inches single mounting facility

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 2nd section front

Throw Quantity:

1 2nd section rear

Mounting Method:

Bracket single mounting facility and unthreaded hole single mounting facility

Features Provided:

Actuator knob

Contact Voltage Rating In Volts:

28.0 dc at sea level

Mounting Facility Pattern:

Four position rectangular single mounting facility

Switch Actuator Indexing Position Quantity:

1 single actuator

Shaft Type:

Round single actuator

Terminal Type:

Tab, solder lug and wire lead

Contact Switching Action:

Breaks before makes each section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

1.0 amperes resistive load ac at sea level

Style Designator:

Circular wafer, bushing mount

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0