

View Online at <https://aerobasegroup.com/nsn/5930-00-817-7726>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Dustproof

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.875 inches

Body Length:

1.094 inches

Body Width:

0.400 inches

Body Height:

0.625 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

0.114 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.406 inches

Actuator Style:

Round

Actuator Diameter:

0.110 inches

Maximum Voltage Rating In Volts:

250.0 ac and 30.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained single switch unit

Switch Release Force:

4.0 ounces

Switch Actuating Force:

14.0 ounces

Actuator Movement:

Between 0.016 pretravel inches and 0.031 overtravel inches and 0.011 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive dc and 15.000 amperes resistive ac

Precious Material And Location:

Contacts gold

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0