NSN 5930-00-818-2335

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-818-2335

Body Style:
Hole mounted
Overall Width:
1.235 inches
Actuator Style:
Roller arm
Actuator Free Position Height:
3.500 inches
Actuator Roller Diameter:
0.500 inches
Actuator Roller Width:
0.125 inches
Housing Height:
1.594 inches
Housing Length:
2.438 inches
Housing Width:
1.235 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Height:
1.906 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:
1.500 inches
Maximum Voltage Rating In Volts:
30.0 dc
Inclosure Type:
Hermetically sealed
Mounting Method:
Unthreaded hole
Features Provided:
Actuator seal
Nonpile-up Contact Arrangement:
2 pole, double throw, double break/double make, permanent jumper, one position momentary single switch unit
Switch Release Force:
32.0 inch-ounces
Switch Actuating Force:
212.8 inch-ounces
Actuator Movement:
Between 11.0 pretravel degrees and 16.0 overtravel degrees and 5.0 differential degrees
Contact Load Current Rating At Maximum Rated Voltage:
5.000 amperes resistive dc and 5.000 amperes inductive dc and 3.000 amperes motor dc

Special Features:

Switch is filled with an inert gas and sealed under pressure

NSN 5930-00-818-2335

Sensitive Switch - Page 2 of 2



Terminal Type A	nd Quantity:
-----------------	--------------

8 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A053a0