

View Online at <https://aerobasegroup.com/nsn/5930-00-820-3119>

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Moisture resistant and salt spray resistant

Overall Length:

3.492 inches

Actuator Style:

Round

Actuator Diameter:

0.250 inches

Actuator Height:

0.652 inches

Actuator Free Position Height:

Between 2.232 inches and 2.292 inches

Housing Diameter:

1.500 inches

Housing Length:

1.200 inches

Housing Bushing Length:

1.000 inches

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Thread Size:

0.625 inches

Nonpile-up Contact Arrangement:

4 pole, double throw, both positions maintained single switch unit

Switch Release Force:

64.0 ounces

Switch Actuating Force:

192.0 ounces

Actuator Movement:

Between 0.040 pretravel inches and 0.500 overtravel inches and 0.030 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc and 4.000 amperes motor dc and 5.000 amperes resistive ac

Thread Series Designator:

Unef

Terminal Type And Quantity:

12 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0