

View Online at <https://aerobasegroup.com/nsn/5930-00-820-3119>

**Body Style:**

Bushing mounted

**Hazardous Locations/environmental Protection:**

Moisture resistant and salt spray resistant

**Overall Length:**

3.492 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.250 inches

**Actuator Height:**

0.652 inches

**Actuator Free Position Height:**

Between 2.232 inches and 2.292 inches

**Housing Diameter:**

1.500 inches

**Housing Length:**

1.200 inches

**Housing Bushing Length:**

1.000 inches

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Thread Size:**

0.625 inches

**Nonpile-up Contact Arrangement:**

4 pole, double throw, both positions maintained single switch unit

**Switch Release Force:**

64.0 ounces

**Switch Actuating Force:**

192.0 ounces

**Actuator Movement:**

Between 0.040 pretravel inches and 0.500 overtravel inches and 0.030 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 3.000 amperes inductive dc and 4.000 amperes motor dc and 5.000 amperes resistive ac

**Thread Series Designator:**

Unef

**Terminal Type And Quantity:**

12 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0