NSN 5930-00-820-5304Toggle Switch - Page 1 of 2



Toggle Switch - Page 1 of 2	
View Online at https://aerobasegroup.com/nsn/5930-00-820-5304	
Body Style:	
Bushing mount	
Overall Length:	
1.312 inches	
Overall Height:	
Between 2.093 inches and 2.183 inches	
Overall Width:	
Between 0.825 inches and 0.855 inches	
Bushing Length:	
Between 0.455 inches and 0.485 inches	
Body Length:	
1.312 inches	
Body Width:	
Between 0.825 inches and 0.855 inches	
Body Height:	
Between 0.963 inches and 0.993 inches	
Actuator Style:	
Round	
Actuator Diameter:	
Between 0.225 inches and 0.255 inches	
Actuator Height:	
Between 1.130 inches and 1.190 inches	
Actuator Position-action Relationship:	
Up position momentary and center position maintained	
Maximum Voltage Rating In Volts:	
250.0 ac and 30.0 dc	
Inclosure Type:	
Fully enclosed	
Mounting Method:	
Threaded bushing	
Thready Qty Per Inch (tpi):	
32	
Thread Size:	
0.469 inches	
Nonpile-up Contact Arrangement:	
4 pole, double throw, one position momentary single switch unit	
Contact Load Commet Bathan At Manhaum Batad Valtage	

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac

Thread Series Designator:

Uns

Terminal Type And Quantity:

12 tab, solder lug

NSN 5930-00-820-5304 Toggle Switch - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0