

View Online at <https://aerobasegroup.com/nsn/5930-00-820-9131>

Body Style:

Bushing mount

Overall Length:

Between 1.250 inches and 1.312 inches

Body Diameter:

Between 0.453 inches and 0.485 inches

Bushing Length:

Between 0.265 inches and 0.297 inches

Case Material:

Ceramic

Actuator Style:

Round

Actuator Diameter:

Between 0.109 inches and 0.141 inches

Actuator Height:

Between 0.312 inches and 0.344 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained

Maximum Voltage Rating In Volts:

120.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

40

Thread Size:

0.250 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

3.000 amperes resistive dc and 1.000 amperes inductive dc and 500.000 milliamperes lamp dc and 3.000 amperes resistive ac and 1.000 amperes inductive ac and 500.000 milliamperes lamp ac

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0