

View Online at <https://aerobasegroup.com/nsn/5930-00-820-9546>

**Body Style:**

Bushing mounted

**Hazardous Locations/environmental Protection:**

Fungus proof and moisture resistant

**Overall Length:**

1.030 inches

**Overall Height:**

0.380 inches

**Overall Width:**

0.380 inches

**Body Diameter:**

0.380 inches

**Bushing Length:**

0.250 inches

**Body Length:**

0.380 inches

**Actuator Diameter:**

0.160 inches

**Actuator Height:**

0.150 inches

**Actuator Color:**

Black single actuator

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**End Application:**

5communications terminal satellite an/gsc-3 (v)1, soruance class dd(963), blue ridge class lcc-19, ship ohio class ssn(trident) , forrestal class cv, guided missile intercept, aircraft stratofortress b-52, aircraft hawkeye e-2c, bullseye, teletype model 28

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.250 inches

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally closed, double break, momentary action single switch unit

**Criticality Code Justification:**

Feat

**Contact Load Current Rating At Maximum Rated Voltage:**

1.000 amperes resistive dc and 1.000 amperes resistive ac

**Special Features:**

Weapons system essential

**Thread Series Designator:**

Unef

**Terminal Type And Quantity:**

2 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0