

View Online at <https://aerobasegroup.com/nsn/5930-00-820-9546>

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Fungus proof and moisture resistant

Overall Length:

1.030 inches

Overall Height:

0.380 inches

Overall Width:

0.380 inches

Body Diameter:

0.380 inches

Bushing Length:

0.250 inches

Body Length:

0.380 inches

Actuator Diameter:

0.160 inches

Actuator Height:

0.150 inches

Actuator Color:

Black single actuator

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

End Application:

5communications terminal satellite an/gsc-3 (v)1, soruance class dd(963), blue ridge class lcc-19, ship ohio class ssn(trident) , forrestal class cv, guided missile intercept, aircraft stratofortress b-52, aircraft hawkeye e-2c, bullseye, teletype model 28

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.250 inches

Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, double break, momentary action single switch unit

Criticality Code Justification:

Feat

Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 1.000 amperes resistive ac

Special Features:

Weapons system essential

Thread Series Designator:

Unef

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0