

View Online at <https://aerobasegroup.com/nsn/5930-00-822-0258>

**Body Style:**

Bushing/hole mounted

**Hazardous Locations/environmental Protection:**

Humidity resistant and shock resistant and vibration resistant

**Overall Length:**

1.250 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.500 inches

**Overall Height:**

2.359 inches

**Overall Width:**

0.938 inches

**Bushing Length:**

0.500 inches

**Body Length:**

1.250 inches

**Body Width:**

0.550 inches

**Case Material:**

Plastic

**Unthreaded Mounting Hole Diameter:**

0.114 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.625 inches

**Actuator Height:**

0.688 inches

**Actuator Free Position Height:**

1.921 inches

**Actuator Adapter Style:**

Pushbutton

**Adapter Bushing Length:**

0.500 inches

**Maximum Voltage Rating In Volts:**

250.0 ac and 30.0 dc

**Inclosure Type:**

Fully enclosed

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

2 two circuit, double break/double make, one position momentary single switch unit

**Switch Release Force:**

3.0 ounces

**Switch Actuating Force:**

28.0 ounces

**Actuator Movement:**

Between 0.060 pretravel inches and 0.018 overtravel inches and 0.028 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

15.000 amperes resistive dc and 10.000 amperes inductive dc and 15.000 amperes resistive ac

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

8 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0