

View Online at <https://aerobasegroup.com/nsn/5930-00-822-0258>

Body Style:

Bushing/hole mounted

Hazardous Locations/environmental Protection:

Humidity resistant and shock resistant and vibration resistant

Overall Length:

1.250 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.500 inches

Overall Height:

2.359 inches

Overall Width:

0.938 inches

Bushing Length:

0.500 inches

Body Length:

1.250 inches

Body Width:

0.550 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

0.114 inches

Actuator Style:

Round

Actuator Diameter:

0.625 inches

Actuator Height:

0.688 inches

Actuator Free Position Height:

1.921 inches

Actuator Adapter Style:

Pushbutton

Adapter Bushing Length:

0.500 inches

Maximum Voltage Rating In Volts:

250.0 ac and 30.0 dc

Inclosure Type:

Fully enclosed

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

2 two circuit, double break/double make, one position momentary single switch unit

Switch Release Force:

3.0 ounces

Switch Actuating Force:

28.0 ounces

Actuator Movement:

Between 0.060 pretravel inches and 0.018 overtravel inches and 0.028 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

15.000 amperes resistive dc and 10.000 amperes inductive dc and 15.000 amperes resistive ac

Thread Series Designator:

Uns

Terminal Type And Quantity:

8 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0