NSN 5930-00-822-1731

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-822-1731

| view Online at https://aerobasegroup.com/hsh/5950-00- |
|---|
| Hazardous Locations/environmental Protection: |
| Raintight and vibration resistant |
| Overall Length: |
| 3.386 inches |
| Overall Height: |
| 5.394 inches |
| Overall Width: |
| 1.181 inches |
| Body Height: |
| 2.456 inches |
| Tempurature Sensing Element Type: |
| Immersion well |
| Operating Tempurature Rating: |
| 199.0 degrees fahrenheit |
| Mounting Method: |
| Immersion well |
| Contact Action Stimulus: |
| Increase |
| Nonpile-up Contact Arrangement: |
| 1 pole, double throw, one position momentary |
| Terminal Type: |
| Tab w/screw |
| Contact Load Current Rating: |
| 0.25 amperes resistive load fourth voltage |
| Contact Adjustability: |
| Actuation point adjustable, preset |
| Contact Adjustment Range: |
| +123.00/+151.00 actuation point degrees fahrenheit |
| Contact Adjustment Type: |
| External actuation point screw |
| Contact Stimulus Rating: |
| 140.00 actuation point degrees fahrenheit |
| Contact Voltage Rating In Volts: |
| 460.0 ac at sea level second voltage |
| Media For Which Designed: |
| Gas or liquid |
| Unpackaged Unit Weight: |
| 0.830 pounds |
| Style Designator: |
| Rectangular |
| Shalf Life: |

N/a

NSN 5930-00-822-1731

Thermostatic Switch - Page 2 of 2



| | | eas | |
|--|--|-----|--|

--

Demilitarization:

No

Fiig:

A048b0