

View Online at <https://aerobasegroup.com/nsn/5930-00-822-5690>

Body Style:

Bushing mount

Overall Length:

Between 0.979 inches and 0.989 inches

Overall Height:

Between 2.046 inches and 2.166 inches

Overall Width:

Between 0.825 inches and 0.855 inches

Bushing Length:

Between 0.465 inches and 0.475 inches

Body Height:

Between 0.916 inches and 0.976 inches

Actuator Style:

Round

Actuator Diameter:

Between 0.235 inches and 0.245 inches

Actuator Height:

Between 0.250 inches and 0.280 inches

Actuator Position-action Relationship:

Up position maintained and center position maintained

Maximum Voltage Rating In Volts:

250.0 ac and 30.0 dc

End Application:

B-52, c-135, c-130

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

3 pole, double throw, both positions maintained single switch unit

Criticality Code Justification:

Feat

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac

Special Features:

Weapon system essential

Thread Series Designator:

Uns

Terminal Type And Quantity:

9 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0