

View Online at <https://aerobasegroup.com/nsn/5930-00-822-5690>

**Body Style:**

Bushing mount

**Overall Length:**

Between 0.979 inches and 0.989 inches

**Overall Height:**

Between 2.046 inches and 2.166 inches

**Overall Width:**

Between 0.825 inches and 0.855 inches

**Bushing Length:**

Between 0.465 inches and 0.475 inches

**Body Height:**

Between 0.916 inches and 0.976 inches

**Actuator Style:**

Round

**Actuator Diameter:**

Between 0.235 inches and 0.245 inches

**Actuator Height:**

Between 0.250 inches and 0.280 inches

**Actuator Position-action Relationship:**

Up position maintained and center position maintained

**Maximum Voltage Rating In Volts:**

250.0 ac and 30.0 dc

**End Application:**

B-52, c-135, c-130

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

3 pole, double throw, both positions maintained single switch unit

**Criticality Code Justification:**

Feat

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac

**Special Features:**

Weapon system essential

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

9 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0