# NSN 5930-00-823-0020

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-823-0020

## Thread Class:

2a single mounting facility

## Thread Length:

0.469 inches single mounting facility

## **Overall Length:**

2.078 inches

#### First Flat Length:

0.438 inches single actuator

#### Flat Height:

0.216 inches single actuator

#### Shaft Diameter:

0.250 inches single actuator

### Shaft Length:

1.000 inches single actuator

### **Overall Diameter:**

1.906 inches

### Individual Section Quantity:

3

Nonturn Device Type:

Slotted bushing at 12: 00 o'clock

## Switch Contact Basic Design:

Nonpile-up symmetrical

#### Pole Quantity:

1 each section front

#### Throw Quantity:

4 each section front

## **Mounting Method:**

Threaded bushing single mounting facility

## Thready Qty Per Inch (tpi):

32 single mounting facility

#### **Thread Size:**

0.469 inches single mounting facility

## Contact Voltage Rating In Volts:

28.0 dc at sea level

## Switch Actuator Indexing Position Quantity:

4 single actuator

## Shaft Type:

Round, flatted single actuator

## **Terminal Type:**

Screw

## **Contact Switching Action:**

Makes before breaks each section front

# NSN 5930-00-823-0020

Rotary Switch - Page 2 of 2



### Switch Actuator Positioning Increment:

45.0 degrees single actuator

#### Switch Actuator Stop Device Type:

Fixed stop single actuator

### **Contact Load Current Rating:**

5.0 amperes resistive load dc at sea level

Style Designator:

Tap, circular, bushing mount

#### **Thread Series Designator:**

Uns single mounting facility

Shelf Life:

N/a

Unit Of Measure:

---

#### Demilitarization:

No

#### Fiig:

A052b0