NSN 5930-00-823-0144

Rotary Switch - Page 1 of 2

Overall Length:



View Online at https://aerobasegroup.com/nsn/5930-00-823-0144

7.625 inches
Overall Height:
7.500 inches
Overall Width:
5.500 inches
First Flat Length:
0.625 inches single actuator
Flat Height:
0.312 inches single actuator
Shaft Diameter:
0.375 inches single actuator
Shaft Length:
0.438 inches single actuator
Unthreaded Mounting Hole Diameter:
0.406 inches single mounting facility
Individual Section Quantity:
6
Knob Manufacturer Code:
80064
Knob Manufacturer Part Number:
900s6202-74095pc1
Longest Horizontal Distance Between Mounting Centers:
3.781 inches single mounting facility
Longest Vertical Distance Between Mounting Centers:
3.781 inches single mounting facility
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
1 each section front
Throw Quantity:
1 each section front
Features Provided:
Actuator knob
Contact Voltage Rating In Volts:
500.0 ac at sea level
Mounting Facility Pattern:
Four position rectangular single mounting facility
Switch Actuator Indexing Position Quantity:
2 single actuator
Shaft Type:
Round, flatted, threaded hole single actuator

NSN 5930-00-823-0144Rotary Switch - Page 2 of 2



Terminal Type:
Threaded stud
Contact Switching Action:
Breaks before makes each section front
Switch Actuator Positioning Increment:
90.0 degrees single actuator
Switch Actuator Stop Device Type:
Adjustable stop single actuator
Contact Load Current Rating:
60.0 amperes resistive load dc at sea level
Style Designator:
Tap, square frame
Test Data Document:
81349-mil-s-15291 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Or Standard:
6sr6a1 type
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Fiig:
A052b0