

View Online at <https://aerobasegroup.com/nsn/5930-00-823-0894>

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Dustproof

Body Diameter:

0.687 inches

Bushing Length:

0.625 inches

Body Length:

1.047 inches

Actuator Style:

Round

Actuator Diameter:

0.250 inches

Actuator Height:

0.250 inches

Actuator Free Position Height:

0.250 inches

Maximum Voltage Rating In Volts:

28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Features Provided:

Actuator seal

Thready Qty Per Inch (tpi):

32

Pile-up Contact Form Arrangement:

2c single position

Thread Size:

0.469 inches

Switch Release Force:

0.5 ounces

Switch Actuating Force:

4.0 ounces

Actuator Movement:

0.406 pretravel inches and 0.187 overtravel inches and 0.093 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 4.000 amperes inductive dc and 4.000 amperes motor dc

Test Data Document:

81349-mils8805 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0