NSN 5930-00-823-2037

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-823-2037

Thread Class: 2a single mounting facility Thread Length: 0.312 inches single mounting facility **Overall Length:** 1.750 inches **Overall Height:** 1.938 inches **Overall Width:** 1.516 inches First Flat Length: 0.250 inches single actuator **Shaft Diameter:** 0.250 inches single actuator **Shaft Length:** 0.437 inches single actuator **Individual Section Quantity:** 1 **Switch Contact Basic Design:** Nonpile-up symmetrical **Pole Quantity:** 1 single section rear **Throw Quantity:** 3 single section rear **Mounting Method:** Threaded bushing single mounting facility **Thread Size:** 0.375 inches single mounting facility **Contact Voltage Rating In Volts:** 28.0 dc at sea level **Switch Actuator Indexing Position Quantity:** 4 single actuator **Shaft Type:** Round, v flatted single actuator **Terminal Type:** Tab, solder lug **Contact Switching Action:** Breaks before makes single section rear **Switch Actuator Positioning Increment:** 60.0 degrees single actuator **Switch Actuator Stop Device Type:**

Fixed-adjustable stops single actuator

NSN 5930-00-823-2037

Rotary Switch - Page 2 of 2



Contact Load Current Rating:

500.0 milliamperes resistive load ac at sea level

Precious Material And Location:

Contact and rotor blade surfaces silver

Precious Material:

Silver

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A052b0