## NSN 5930-00-823-2052

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-823-2052

#### **Thread Class:**

2b single mounting facility

## Hazardous Locations/environmental Protection:

Dustproof

## **Overall Length:**

3.750 inches

#### **Overall Height:**

4.125 inches

#### **Overall Width:**

4.125 inches

#### First Flat Length:

0.875 inches single actuator

#### Flat Height:

0.316 inches single actuator

#### Shaft Diameter:

0.375 inches single actuator

## Shaft Length:

1.125 inches single actuator

## Individual Section Quantity:

2

## Knob Manufacturer Code:

82121

## Knob Manufacturer Part Number:

8164-12y

#### Longest Horizontal Distance Between Mounting Centers:

2.281 inches single mounting facility

#### Longest Vertical Distance Between Mounting Centers:

2.281 inches single mounting facility

#### Switch Contact Basic Design:

Nonpile-up symmetrical

#### **Pole Quantity:**

1 each section rear

#### **Throw Quantity:**

3 each section rear

#### **Mounting Method:**

Bracket single mounting facility and threaded hole single mounting facility

#### **Features Provided:**

Actuator knob

## Thready Qty Per Inch (tpi):

20 single mounting facility

#### **Thread Size:**

0.250 inches single mounting facility

# NSN 5930-00-823-2052

Rotary Switch - Page 2 of 2



**Contact Voltage Rating In Volts:** 500.0 ac at sea level **Switch Actuator Momentary Position:** Clockwise single actuator and counterclockwise single actuator Mounting Facility Pattern: Four position rectangular single mounting facility **Switch Actuator Indexing Position Quantity:** 3 single actuator Shaft Type: Round, flatted, threaded hole single actuator **Terminal Type:** Tab w/screw **Contact Switching Action:** Breaks before makes each section front **Switch Actuator Positioning Increment:** 90.0 degrees single actuator Switch Actuator Stop Device Type: Adjustable stop single actuator **Contact Load Current Rating:** 30.0 amperes resistive load ac at sea level **Special Features:** Shaft is rd, flatted, thd hole and pin type Style Designator: Tap, circuit selector **Thread Series Designator:** Unc single mounting facility Shelf Life: N/a Unit Of Measure: --**Demilitarization:** No Fiig: A052b0