NSN 5930-00-823-2054

Sensitive Switch - Page 1 of 2

0.138 inches



View Online at https://aerobasegroup.com/nsn/5930-00-823-2054

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Dustproof
Overall Length:
3.125 inches
Overall Height:
3.875 inches
Overall Width:
1.125 inches
Case Material:
Plastic
Actuator Length:
1.570 inches
Actuator Style:
Roller arm
Actuator Free Position Height:
2.850 inches
Actuator Roller Diameter:
Between 0.720 inches and 0.780 inches
Actuator Roller Width:
Between 0.282 inches and 0.342 inches
Housing Height:
Between 1.720 inches and 1.780 inches
Housing Length:
2.740 inches
Housing Width:
1.000 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:
1.000 inches
Maximum Voltage Rating In Volts:
600.0 ac and 250.0 dc
End Application:
C-130 hercules aircraft, support equipment c-5, f-106, b-52 aircraft.
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Thready Qty Per Inch (tpi):
32
Thread Size:

NSN 5930-00-823-2054

Sensitive Switch - Page 2 of 2

A053a0



Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:
6.0 ounces
Criticality Code Justification:
Feat
Switch Actuating Force:
Between 10.0 ounces and 20.0 ounces
Actuator Movement:
Between 0.188 pretravel inches and 0.219 overtravel inches and 0.006 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
250.000 milliamperes resistive dc and 2.000 amperes resistive ac
Special Features:
Weapon system essential
Thread Series Designator:
Unc
Terminal Type And Quantity:
3 screw
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: