## NSN 5930-00-823-2114

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-823-2114

view Online at https://aerobasegroup.com/nsn/5950-00-625-2114
Thread Class:
2b single mounting facility
Hazardous Locations/environmental Protection:
Dustproof
Overall Length:
5.000 inches
Overall Height:
4.125 inches
Overall Width:
4.125 inches
First Flat Length:
0.875 inches single actuator
Flat Height:
0.312 inches single actuator
Shaft Diameter:
0.375 inches single actuator
Shaft Length:
1.250 inches single actuator
Individual Section Quantity:
3
Knob Manufacturer Code:
82121
Knob Manufacturer Part Number:
8164-12y
Longest Horizontal Distance Between Mounting Centers:
2.281 inches single mounting facility
Longest Vertical Distance Between Mounting Centers:
2.281 inches single mounting facility
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
1 each section front
Throw Quantity:
2 each section rear
Mounting Method:
Bracket single mounting facility and threaded hole single mounting facility
Features Provided:
Actuator knob
Thready Qty Per Inch (tpi):
20 single mounting facility

Thread Size:

0.114 inches single mounting facility

## **NSN 5930-00-823-2114**Rotary Switch - Page 2 of 2



Contact Voltage Rating In Volts:
500.0 ac at sea level
Rotor Through Connection Quantity:
1 each section
Mounting Facility Pattern:
Four position rectangular single mounting facility
Switch Actuator Indexing Position Quantity:
3 single actuator
Shaft Type:
Round, flatted, threaded hole single actuator
Terminal Type:
Tab w/screw
Contact Switching Action:
Breaks before makes each section rear
Switch Actuator Positioning Increment:
90.0 degrees single actuator
Switch Actuator Stop Device Type:
Adjustable stop single actuator
Contact Load Current Rating:
30.0 amperes resistive load ac at sea level
Style Designator:
Tap, circuit selector
Thread Series Designator:
Unc single mounting facility
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A052b0