

View Online at <https://aerobasegroup.com/nsn/5930-00-823-2115>

Body Style:

Panel mount

Overall Length:

1.375 inches

Overall Height:

Between 0.622 inches and 0.624 inches

Overall Width:

Between 0.622 inches and 0.624 inches

Body Diameter:

Between 0.552 inches and 0.572 inches

Body Length:

Between 0.888 inches and 0.920 inches

Actuator Diameter:

Between 0.355 inches and 0.395 inches

Actuator Height:

Between 0.235 inches and 0.265 inches

Actuator Color:

Red single actuator

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Features Provided:

Actuator seal

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, double make, momentary action, with contact on arm single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive dc and 3.000 amperes inductive dc and 3.000 amperes lamp dc and 10.000 amperes resistive ac and 5.000 amperes inductive ac and 3.000 amperes lamp ac

Test Data Document:

81349-mil-s-8805 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

3 tab, solder lug

Specification Data:

81349-mil-s-8805/3 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A053a0