

View Online at <https://aerobasegroup.com/nsn/5930-00-823-6099>

Thread Class:

2a single mounting facility

Thread Length:

0.165 inches single mounting facility and 0.297 inches single mounting facility

Overall Length:

3.281 inches

Overall Height:

Between 1.296 inches and 1.328 inches

Overall Width:

Between 1.296 inches and 1.328 inches

First Flat Length:

0.359 inches single actuator and 0.391 inches single actuator

Flat Height:

0.140 inches single actuator and 0.172 inches single actuator

Shaft Diameter:

0.234 inches single actuator and 0.266 inches single actuator

Shaft Length:

0.781 inches single actuator

Nonturn Device Radius:

0.500 inches at 9:00 o'clock

Individual Section Quantity:

3

Nonturn Device Type:

Pin at 9:00 o'clock

Operating Temperature Range:

-55.0/+85.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

2 each section front

Throw Quantity:

6 each section front

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

115.0 ac at sea level

Switch Actuator Indexing Position Quantity:

6 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Turret

Contact Switching Action:

Breaks before makes each section front

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Contact Load Current Rating:

1.0 amperes resistive load ac at sea level

Precious Material And Location:

Contacts gold and terminals silver

Precious Material:

Gold and silver

Style Designator:

Tap, square frame

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0