# NSN 5930-00-823-6119

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-823-6119

## **Thread Class:**

2a single mounting facility

## **Thread Length:**

0.275 inches single mounting facility and 0.297 inches single mounting facility

## Hazardous Locations/environmental Protection:

Moisture resistant

## **Overall Length:**

Between 1.858 inches and 1.954 inches

#### **Overall Height:**

Between 1.296 inches and 1.328 inches

## **Overall Width:**

Between 1.296 inches and 1.328 inches

## First Flat Length:

0.359 inches single actuator and 0.391 inches single actuator

## Flat Height:

0.140 inches single actuator and 0.172 inches single actuator

## Shaft Diameter:

0.234 inches single actuator and 0.266 inches single actuator

## Shaft Length:

0.749 inches single actuator and 0.813 inches single actuator

## Nonturn Device Radius:

0.484 inches at 9: 00 o'clock and 0.516 inches at 9: 00 o'clock

## Individual Section Quantity:

1

## Nonturn Device Type:

Pin at 9: 00 o'clock

## **Operating Tempurature Range:**

-55.0/+85.0 degrees celsius

## Switch Contact Basic Design:

Nonpile-up symmetrical

## Pole Quantity:

1 single section rear

## **Throw Quantity:**

9 single section rear

## **Mounting Method:**

Threaded bushing single mounting facility

## Thready Qty Per Inch (tpi):

32 single mounting facility

## Thread Size:

0.375 inches single mounting facility

## **Contact Voltage Rating In Volts:**

115.0 ac at sea level

# NSN 5930-00-823-6119

Rotary Switch - Page 2 of 2



**Switch Actuator Indexing Position Quantity:** 9 single actuator Shaft Type: Round, flatted single actuator **Terminal Type:** Turret **Contact Switching Action:** Breaks before makes single section rear **Switch Actuator Positioning Increment:** 30.0 degrees single actuator **Contact Load Current Rating:** 1.0 amperes resistive load ac at sea level **Precious Material And Location:** Contacts gold and terminals silver **Precious Material:** Gold and silver Style Designator: Tap, square frame **Thread Series Designator:** Uns single mounting facility Shelf Life: N/a

Unit Of Measure:

---

**Demilitarization:** 

No

Fiig:

A052b0