

View Online at <https://aerobasegroup.com/nsn/5930-00-824-3710>

Hazardous Locations/environmental Protection:

Moisture resistant and vibration resistant and dustproof

Overall Length:

1.620 inches

Overall Height:

1.093 inches

Unthreaded Mounting Hole Diameter:

0.128 inches

Distance Between Mounting Facility Centers:

1.260 inches

Pressure Switch Type:

Gage

Operating Tempurature Rating:

Between -40.0 degrees fahrenheit and 185.0 degrees fahrenheit

Mounting Method:

Unthreaded hole

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained

Terminal Type:

Tab, solder lug

Contact Load Current Rating:

5.0 amperes resistive load first voltage and 3.0 amperes inductive load first voltage5.0 amperes resistive load second voltage and 5.0 amperes inductive load second voltage

Contact Adjustability:

Actuation point not adjustable and deactuation point not adjustable

Contact Voltage Rating In Volts:

28.0 dc at sea level first voltage115.0 ac at sea level second voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Disc w/flange

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0