

View Online at <https://aerobasegroup.com/nsn/5930-00-824-3710>

**Hazardous Locations/environmental Protection:**

Moisture resistant and vibration resistant and dustproof

**Overall Length:**

1.620 inches

**Overall Height:**

1.093 inches

**Unthreaded Mounting Hole Diameter:**

0.128 inches

**Distance Between Mounting Facility Centers:**

1.260 inches

**Pressure Switch Type:**

Gage

**Operating Temperature Rating:**

Between -40.0 degrees fahrenheit and 185.0 degrees fahrenheit

**Mounting Method:**

Unthreaded hole

**Contact Action Stimulus:**

Increase

**Mounting Facility Pattern:**

Two position in-line

**Nonpile-up Contact Arrangement:**

1 pole, double throw, both positions maintained

**Terminal Type:**

Tab, solder lug

**Contact Load Current Rating:**

5.0 amperes resistive load first voltage and 3.0 amperes inductive load first voltage5.0 amperes resistive load second voltage and 5.0 amperes inductive load second voltage

**Contact Adjustability:**

Actuation point not adjustable and deactuation point not adjustable

**Contact Voltage Rating In Volts:**

28.0 dc at sea level first voltage115.0 ac at sea level second voltage

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Disc w/flange

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0