

View Online at <https://aerobasegroup.com/nsn/5930-00-824-3909>

Thread Class:

2a single mounting facility

Thread Length:

0.370 inches single mounting facility

Overall Length:

1.460 inches

First Flat Length:

0.250 inches single actuator

Flat Height:

0.216 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.340 inches single actuator

Overall Diameter:

1.156 inches

Nonturn Device Radius:

0.370 inches at 12: 00 o'clock

Individual Section Quantity:

1

Nonturn Device Type:

Tab at 12: 00 o'clock

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 single section front

Throw Quantity:

4 single section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

30.0 lowest dc voltage rating at sea level

Rotor Through Connection Quantity:

1 single section

Switch Actuator Indexing Position Quantity:

4 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes single section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

750.0 milliamperes resistive load lowest dc voltage rating at sea level

Precious Material And Location:

Terminals and rotor contacts silver and terminal surfaces gold

Precious Material:

Silver and gold

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A052b0