

View Online at <https://aerobasegroup.com/nsn/5930-00-824-8761>

**Thread Class:**

2a 1st mounting facility

**Thread Length:**

0.312 inches 1st mounting facility

**Hazardous Locations/environmental Protection:**

Moisture proof

**Overall Length:**

2.347 inches

**First Flat Length:**

0.040 inches single actuator

**Flat Height:**

0.094 inches single actuator

**Shaft Diameter:**

0.125 inches single actuator

**Shaft Length:**

0.109 inches single actuator

**Overall Diameter:**

0.687 inches

**Unthreaded Mounting Hole Diameter:**

0.125 inches 2nd mounting facility

**Nonturn Device Radius:**

0.260 inches at 3:00 o'clock

**Individual Section Quantity:**

4

**Nonturn Device Type:**

Tab at 3:00 o'clock

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 each section front

**Throw Quantity:**

6 each section rear

**Mounting Method:**

Threaded bushing 1st mounting facility

**Thread Size:**

0.250 inches 1st mounting facility

**Contact Voltage Rating In Volts:**

125.0 ac at sea level

**Switch Actuator Indexing Position Quantity:**

6 single actuator

**Shaft Type:**

Round, slotted, flatted single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes each section rear

**Switch Actuator Positioning Increment:**

36.0 degrees single actuator

**Contact Load Current Rating:**

0.25 amperes resistive load ac at sea level

**Style Designator:**

Tap, circular, bushing mount

**Thread Series Designator:**

Unef 1st mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0