
## NSN 5930-00-826-0172

Lever Switch - Page 1 of 2

**Thread Class:** 

2a





## **Body Style:** Bushing mounted **Bushing Length:** Between 0.484 inches and 0.516 inches **Body Length:** Between 1.922 inches and 1.953 inches **Body Width:** Between 0.651 inches and 0.656 inches **Body Height:** Between 1.234 inches and 1.266 inches **Actuator Style:** Round **Actuator Diameter:** 0.312 inches **Actuator Height:** Between 1.312 inches and 1.438 inches **Actuator Position-action Relationship:** Up position maintained and down position momentary and center position maintained **Actuator Color:** Black single actuator Maximum Voltage Rating In Volts: 125.0 ac **Inclosure Type:** Uninclosed **Mounting Method:** Threaded bushing Thready Qty Per Inch (tpi): 20 **Pile-up Contact Form Arrangement:** 1c 2nd position **Thread Size:** 0.500 inches Contact Load Current Rating At Maximum Rated Voltage: 1.000 amperes resistive ac **Thread Series Designator:** Unf **Terminal Type And Quantity:** 6 tab, solder lug Shelf Life: N/a

## NSN 5930-00-826-0172

Lever Switch - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A053a0

