

View Online at <https://aerobasegroup.com/nsn/5930-00-826-3348>

**Thread Class:**

2a

**Body Style:**

Bushing mounted

**Overall Length:**

0.980 inches

**Overall Height:**

0.375 inches

**Overall Width:**

0.375 inches

**Body Diameter:**

Between 0.372 inches and 0.378 inches

**Bushing Length:**

Between 0.247 inches and 0.253 inches

**Case Material:**

Metal

**Actuator Style:**

Round

**Actuator Diameter:**

Between 0.130 inches and 0.170 inches

**Actuator Height:**

0.160 inches

**Actuator Color:**

Black single actuator

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Features Provided:**

Actuator seal

**Thread Size:**

0.250 inches

**Nonpile-up Contact Arrangement:**

1 pole, single throw, both positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

1.000 amperes resistive dc and 250.000 milliamperes inductive dc and 250.000 milliamperes lamp dc and 1.000 amperes resistive ac and 250.000 milliamperes inductive ac and 250.000 milliamperes lamp ac

**Test Data Document:**

81349-mil-s-8805 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

UNF

**Terminal Type And Quantity:**

2 tab, solder lug

**Specification Data:**

81349-mil-s-8805/3 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0