# NSN 5930-00-826-3475

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-826-3475

## **Thread Class:**

2a single mounting facility

#### Thread Length:

0.380 inches single mounting facility

## **Overall Length:**

4.320 inches

#### **Overall Height:**

2.810 inches

#### **Overall Width:**

2.000 inches

#### First Flat Length:

0.380 inches single actuator

#### Flat Height:

0.218 inches single actuator

#### Shaft Diameter:

0.250 inches single actuator

# Shaft Length:

0.500 inches single actuator

## Individual Section Quantity:

3

### **Operating Tempurature Range:**

-0.0/+55.0 degrees celsius

#### Switch Contact Basic Design:

Nonpile-up symmetrical

#### **Pole Quantity:**

3 each section front

#### **Throw Quantity:**

3 each section front

#### **Mounting Method:**

Threaded bushing single mounting facility

#### **Thread Size:**

0.375 inches single mounting facility

#### **Contact Voltage Rating In Volts:**

28.0 dc at sea level

#### Shaft Flat/slot Angular Location:

295.0 degrees from contact position 1 single actuator

# Switch Actuator Indexing Position Quantity:

3 single actuator

#### Shaft Type:

Round, flatted single actuator

#### **Terminal Type:**

Tab, solder lug

# NSN 5930-00-826-3475

Rotary Switch - Page 2 of 2



**Contact Switching Action:** Breaks before makes each section front Switch Actuator Positioning Increment: 40.0 degrees single actuator **Contact Load Current Rating:** 5.0 amperes resistive load ac at sea level **Precious Material And Location:** Contacts silver **Precious Material:** Silver Style Designator: Circular wafer, bushing mount **Thread Series Designator:** Unef single mounting facility Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A052b0