## NSN 5930-00-827-0907

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-827-0907

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Oiltight
Overall Length:
4.875 inches
Overall Height:
1.781 inches
Overall Width:
1.531 inches
Actuator Style:
Roller plunger
Actuator Free Position Height:
2.031 inches
Actuator Roller Diameter:
0.500 inches
Housing Height:
1.781 inches
Housing Length:
4.156 inches
Housing Width:
1.531 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:
2.344 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Width:
1.156 inches
Maximum Voltage Rating In Volts:
600.0 ac and 600.0 dc
Inclosure Type:
Fully enclosed
Features Provided:
Actuator seal
Nonpile-up Contact Arrangement:
1 two circuit, double break/double make, one position momentary single switch unit
Switch Actuating Force:
56.0 ounces
Actuator Movement:

0.075 pretravel inches and 0.127 overtravel inches and 0.030 differential inches

Contact Load Current Rating At Maximum Rated Voltage: 0.100 amperes resistive dc and 1.200 amperes resistive ac

**Precious Material And Location:** 

Contacts silver

## **NSN 5930-00-827-0907** Sensitive Switch - Page 2 of 2



reminal Type And Quantity:	
4 screw	
Shelf Life:	
N/a	
Unit Of Measure:	
-	
Demilitarization:	
No	

Fiig: A053a0