

View Online at <https://aerobasegroup.com/nsn/5930-00-827-1559>

Inside Diameter:

0.250 inches single connection

Hazardous Locations/environmental Protection:

Vibration resistant

Overall Length:

5.000 inches

Overall Height:

10.125 inches

Overall Width:

4.000 inches

Mounting Slot Width:

0.344 inches

Body Height:

8.375 inches

Longest Horizontal Distance Between Mounting Centers:

2.750 inches

Longest Vertical Distance Between Mounting Centers:

8.625 inches

Pressure Switch Type:

Gage

Mounting Method:

Bracket and slot

Features Provided:

Electrical access port

Contact Action Stimulus:

Increase

Proof Pressure:

280.00 pounds per square inch

Thread Size:

0.250 inches single pressure connection

Mounting Facility Pattern:

Four position rectangular

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Screw

Contact Load Current Rating:

5.0 amperes resistive load first voltage

Contact Adjustability:

Actuation point adjustable

Contact Adjustment Range:

+0.00/+140.00 actuation point pounds per square inch

Contact Adjustment Type:

External actuation point screw

Contact Voltage Rating In Volts:

600.0 ac at sea level second voltage

Pressure Connector Type:

Swivel nut, inverted flare, threaded internal single connection

Media For Which Designed:

Gas or liquid

Precious Material And Location:

Contacts silver

Precious Material:

Silver

Style Designator:

Rectangular w/bracket

Thread Series Designator:

Nptf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0