

View Online at <https://aerobasegroup.com/nsn/5930-00-827-3986>

**Body Style:**

Bushing mount

**Hazardous Locations/environmental Protection:**

Submersible

**Overall Length:**

1.640 inches

**Overall Width:**

1.350 inches

**Bushing Length:**

0.470 inches

**Body Length:**

1.640 inches

**Body Width:**

1.350 inches

**Body Height:**

1.320 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.245 inches

**Actuator Height:**

0.680 inches

**Actuator Position-action Relationship:**

Up position maintained and down position momentary and center position maintained

**Actuator Position-locking Relationship:**

Up position locked in and out and down position no locking action and center position no locking action

**Maximum Voltage Rating In Volts:**

200.0 ac and 250.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

4 pole, double throw, one position momentary, two positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

0.500 amperes resistive dc and 6.000 amperes resistive ac

**Special Features:**

Incl. Integral lock f0r actuat0r

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

12 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0