## NSN 5930-00-827-5131

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-827-5131

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Dustproof
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.000 inches
Body Length:
1.940 inches
Body Width:
0.687 inches
Body Height:
1.020 inches
Case Material:
Plastic
Unthreaded Mounting Hole Diameter:
0.150 inches
Actuator Style:
Roller plunger
Actuator Free Position Height:
Between 1.220 inches and 1.250 inches
Actuator Roller Diameter:
Between 0.230 inches and 0.240 inches
Actuator Roller Width:
0.250 inches
Maximum Voltage Rating In Volts:
460.0 ac and 250.0 dc
Inclosure Type:
Fully enclosed
Nonpile-up Contact Arrangement:
1 pole, double throw, both positions maintained single switch unit
Switch Release Force:
4.0 ounces
Switch Actuating Force:
12.0 ounces
Actuator Movement:
Between 0.015 pretravel inches and 0.100 overtravel inches and 0.0005 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
250.000 milliamperes resistive dc and 15.000 amperes resistive ac
Terminal Type And Quantity:
3 screw
Shelf Life:
N/a

## NSN 5930-00-827-5131

Sensitive Switch - Page 2 of 2



		• •			
ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

Yes - demil/mli

Fiig:

A053a0