

View Online at <https://aerobasegroup.com/nsn/5930-00-827-5131>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Dustproof

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.000 inches

Body Length:

1.940 inches

Body Width:

0.687 inches

Body Height:

1.020 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

0.150 inches

Actuator Style:

Roller plunger

Actuator Free Position Height:

Between 1.220 inches and 1.250 inches

Actuator Roller Diameter:

Between 0.230 inches and 0.240 inches

Actuator Roller Width:

0.250 inches

Maximum Voltage Rating In Volts:

460.0 ac and 250.0 dc

Inclosure Type:

Fully enclosed

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained single switch unit

Switch Release Force:

4.0 ounces

Switch Actuating Force:

12.0 ounces

Actuator Movement:

Between 0.015 pretravel inches and 0.100 overtravel inches and 0.0005 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

250.000 milliamperes resistive dc and 15.000 amperes resistive ac

Terminal Type And Quantity:

3 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A053a0