## NSN 5930-00-827-9537

Lever Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-827-9537 **Thread Class:** 2a **Body Style: Bushing mounted Overall Length:** 3.562 inches **Overall Height:** 1.156 inches **Overall Width:** 0.750 inches **Bushing Length:** 0.312 inches **Body Width:** 0.750 inches **Body Height:** 1.156 inches **Actuator Style:** Round **Actuator Height:** 1.000 inches **Actuator Position-action Relationship:** Up position maintained and down position maintained and center position momentary **Actuator Position-locking Relationship:** Up position locked in and out and down position locked in and out and center position no locking action **Actuator Color:** Black single actuator **Maximum Voltage Rating In Volts:** 110.0 ac **Inclosure Type:** Uninclosed **Mounting Method:** Threaded bushing Thready Qty Per Inch (tpi): 32 **Pile-up Contact Form Arrangement:** 1c 2nd position **Thread Size:** 0.375 inches

Contact Load Current Rating At Maximum Rated Voltage:

3.000 amperes resistive ac

## Test Data Document:

03538-7742847+003 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

## NSN 5930-00-827-9537

Lever Switch - Page 2 of 2



ınread	Series	Designator
Unef		

**Terminal Type And Quantity:** 

6 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0